



K2 MIG 250

Portable single-phase MIG welding power source with built-in wire feeding unit from K2 by Kemppi range. Multi-process power source for MIG/MAG, TIG and MMA welding.

Applications

- Thin sheet metal fabrication
- Installation and outfitting
- Workshops

★ Key Highlights

- Inverter-based single-phase machine
- Supports basic MIG/MAG, MMA and TIG welding
- Digital display of current and voltage
- 4-roll wire feed mechanism
- Dynamics and arc force control
- Built-in hot start
- Maximum wire spool capacity of 300mm
- Suitable for use with power generators

🔍 Technical Specifications

K2		MIG 250
Connection voltage	1 [~] , 50/60 Hz	230V
Current range MIG/MAG	A	30-250
Current range TIG	A	10-200
Current range MMA	A	10-200
Open circuit voltage	V	60-70
Filler wire	mm	0.6-1.0
Wire feed speed	m/min	2-16
Duty cycle MIG		35% / 250A @ 40°C
Duty cycle MMA/TIG		35% / 200A @ 40°C
Display		Digital display
Wire spool size	mm	300
Wire feed mechanism		4-roll
Cooling		Forced air cooling
Dimensions	L x W x H (mm)	540 x 280 x 353
Weight	kg	22



Similar Products



K2 MMA 200



K2 MMA 400



K2 PLASMA 40



The Basic Welding Expert

Inspired by the mighty K2 mountain of the Karakoram range, **K2 by Kemppi** challenges the welding industry by setting new benchmarks in basic welding that expand capabilities at affordable prices.

www.k2welding.net

