



K2 MMA 400

Rough and robust arc welding power source from K2 by Kemppi range. Suitable for all types of MMA electrodes with advanced functions for better arc ignition and arc force control. Suitable for outdoor use with generators.

Applications

- Installation and outfitting
- Repair and maintenance
- Metal workshops
- Chemical and process industry
- Shipyards and offshore industry

🛠 Key Highlights

- Inverter-based three-phase high performance MMA welding solution
- Powerful and portable MMA welder
- Suitable for workshop and site applications
- Contact ignition DC TIG (Lift TIG)
- Hot start and arc force adjustment for optimized starts and arc control
- Smooth and consistent welding
- Suitable for use with power generators

Q Technical Specifications

К2		MMA 400
Connection voltage	3~, 50/60 Hz	400V
Current range	А	20-400
Open circuit voltage	V	70-80
Stick electrode	Ø	1.5-6.0mm
Duty cycle MMA/TIG		40% / 400A @ 40°C
Display		Digital display
Hot start		Yes
Arc force		Yes
Cooling		Forced air cooling
Dimensions	L x W x H (mm)	560 x 260 x 460
Weight	kg	23



Product Range









The Basic Welding Expert

Inspired by the mighty K2 mountain of the Karakoram range, **K2 by Kemppi** challenges the welding industry by setting new benchmarks in basic welding that expand capabilities at affordable prices.

www.k2welding.net