



K2 MMA 200 PFC

Small but Mighty



K2 MMA 200 PFC is an inverter-based single-phased MMA and (Lift) TIG power source. Lightweight and portable machine which is suitable for all types of MMA electrodes.



Key benefits

- Built-in anti-stick, hot start and arc force for optimized starts and arc control
- High duty-cycle, 40% at 200 A
- Multi-voltage 110V / 230V



Applications

- Repair and maintenance
- Agriculture
- Metal workshops
- Chemical and process industry



Technical Specifications

K2 MMA 200 PFC		MMA		TIG
Input voltage	V	110 V 230 V	30.5 28.5	18.5 19.5
Rated input power	kVA	110 V 230 V	3.33 6.53	2.03 4.42
Duty cycle	A		110 V: 40 % 110 A 110 V: 60 % 90 A 110 V: 100 % 70 A	230 V: 40 % 200 A 230 V: 60 % 160 A 230 V: 100 % 130 A
Welding current range	A	110 V: 10-110 230 V: 10-200		
Power factor		0.99		
No-load voltage	V	70		
Protection class		IP21S		
Electrode diameter	Ø mm	1.6-5.0		
Electrode type		6010, 6011, 6013, 7018, etc.		
Cooling		AF		
Dimensions (mm)	L x W x H	450 x 160 x 310		
Weight	kg	6.5		

The Basic Welding Expert

By offering quality, efficiency, and value for money in one range, K2 by Kemppi sets a new standard for basic welding. The K2 by Kemppi range offers a comprehensive product portfolio of power sources for MMA, MIG, TIG welding. The power sources are bundled with torches of Trafimet a Kemppi Company, Italy – the world leader in torches over the last four decades, and a part of the Kemppi Group.

