

K2 MMA 200 PFC

Small but Mighty



K2 MMA 200 PFC is an inverter-based single-phased MMA and (Lift) TIG power source. Lightweight and portable machine which is suitable for all types of MMA electrodes.



- Built-in anti-stick, hot start and arc force for optimized starts and arc control
- High duty-cycle, 40% at 200 A
- Multi-voltage 110V / 230V
- 2-Year Warranty

Applications

- Repair and maintenance
- Agriculture

- Metal workshops
- Chemical and process industry



Technical Specifications

CE ISO 14001:2015 GB/T 19001-2016/ISO 9001:2015 ISO 45001:2018

| K2 MMA 200 PFC | | | MMA | TIG |
|-----------------------|-----------|---------------------------------|--|--|
| Input voltage | V | 110 V 230 V | 30.5 28.5 | 18.5 19.5 |
| Rated input power | kVA | 110 V 230 V | 3.33 6.53 | 2.03 4.42 |
| Duty cycle | A | | 110 V: 40 % 110 A 110 V: 60 % 90 A 110 V: 100 % 70 A | 230 V: 40 % 200 A 230 V: 60 % 160 A 230 V: 100 % 130 A |
| Welding current range | А | 110 V: 10-110 230 V: 10-200 | | |
| Power factor | | 0.99 | | |
| No-load voltage | V | 70 | | |
| Protection class | | IP21S | | |
| Electrode diameter | Ø mm | 1.6-5.0 | | |
| Electrode type | | 6010, 6011, 6013, 7018, etc. | | |
| Cooling | | AF | | |
| Dimensions (mm) | L x W x H | 450 x 160 x 310 | | |
| Weight | kg | 6.5 | | |

The Basic Welding Expert

By offering quality, efficiency, and value for money in one range, K2 by Kemppi sets a new standard for basic welding. The K2 by Kemppi range offers a comprehensive product portfolio of power sources for MMA, MIG, TIG welding. The power sources are bundled with torches of Trafimet a Kemppi Company, Italy – the world leader in torches over the last four decades, and a part of the Kemppi Group.



k2welding.net